

LoRa® SPY T2



Temperature recorder with a long-range LoRaWAN™ connectivity



Presentation

The LoRa® SPYT2 measures and records temperature thanks to an external probe. Data are sent to the JRI secure Cloud by LoRaWAN™ network of the telecom operators members of the LoRa Alliance™, or by a local network. In case of threshold excursions, real-time alerts are sent.

Designed to monitor thermo-controlled chambers, the LoRa® SPY T2 can be fixed outside thanks to its magnet allowing to visualize data measurement.

Technical features

	Standard version	Incubator version	
Interface	Status LED lights, On/Off touch sensitive button, LCD display		
Measurement range	-50°C to +105°C		
Accuracy	$\pm 0.3^{\circ}$ C from -20° C to $+30^{\circ}$ C $\pm 0.5^{\circ}$ C out of this range	$\pm 0.2^{\circ}$ C from $+30^{\circ}$ C to $+50^{\circ}$ C $\pm 0.5^{\circ}$ C out of this range	
Memory	10 000 data points		
Communication frequency	868 MHz / 915 MHz		
Radio range	Up to 16 km open field range		
Sensor	External Class A PT 100 - Ø5x20mm		
Resolution	0.01		
Measuring interval	Adjustable from 1 mn to 5 mn		
Transmission & recording interval (internal memory)	Adjustable from 1 mn to 24 hrs		
Response time σ_{90}	~2 mn		
Operating conditions	-30°C to +70°C		
Protection	IP65		
Case	Polycarbonate – Food contact		
Dimensions and weight	87 x 64 x 25 mm / ~ 100 g		
Cable length	30 cm and 3 m		
Power supply	Replaceable Lithium 3,6v battery		
Battery lifetime	2 years		
Fixation	Fixing eyelets and integrated magnets		
Supplied with	Blue and green identification rings	Yellow identification ring	
	User manual on www.jri-corp.com		
Compliance	CE, ROHS, FCC, EN 300-320, NF EN 12830		
Standard calibration points	-18°C/+5°C/+25°C	+36C/+38°C/+50°C	

Benefits

Easy-to-use The recorder is ready-to-use and has operating and alarm lights




- Excellent measurement accuracy
- Several modes of data exploitation



eyelets and integrated magnets Replaceable battery

External temperature probe





Freezer Standard



1/2

17 349b EN 01 06

JRI, SAS

Logistics Pole / 2 Rue de la Voivre / PA Technoland / BP 21 / 25490 FESCHES LE CHÂTEL / France SIRET 380 332 858 00030 - Ph.: +33 (0)3 81 30 68 04 / sales@group-mms.com

Part Nrs

	868 MHz		915 MHz	
	With battery	Without battery	Without battery	
STANDARD VERSION				
LoRa SPY T2 30cm	11804 EU	11804 EX	12269 EX	
LoRa SPY T2 3m	11805 EU	11805 EX	12271 EX	
INCUBATOR VERSION				
LoRa SPY T2 30cm	11804_I EU	11804_I EX	12269_I EX	
LoRa SPY T2 3m	11805_I EU	11805_I EX	12271_I EX	