

I

Presentation

The Nano SPY T2 measures and records temperature with its external probe. It transmits the data to a nearby LINK module via 2.4 GHz radio frequency communication.

Mini Temperature Data logger

2,4GHz radiofrequency communication

The data are then automatically sent to the JRI secure Cloud for hosting, and will be managed from the JRI MySirius web application.

If thresholds are exceeded, alerts are transmitted in real time to react immediately.

Designed to monitor thermo-controlled chambers, the sensor can be fixed thanks to its magnet outside of the equipment.



	Standard Version	Incubator Version
Interface	Status LED and On/Off touch sensitve button	
Measurement range	-50°C to +105°C	
Accuracy	$\pm 0.3^{\circ}$ C from -20°C to +30°C and $\pm 0.5^{\circ}$ C out of this range	$\pm 0.2^{\circ}$ C from $+30^{\circ}$ C to $+50^{\circ}$ C and $\pm 0.5^{\circ}$ C out of this range
Communication frequency	2,4 GHz (802.15.4)	
Memory	10 000 data points	
Temperature sensor	External PT100 probe - Ø5x20mm	
Operating conditions	-30°C to +70°C	
Resolution	0.01	
Measuring and transmission period	1 mn	
Internal memory recording period	Adjustable from 1 mn to 24 hrs	
Response time σ_{90}	\sim 2 mn at 90% of the variation	
Protection	IP65	
Case	Polycarbonate – Food contact	
Dimensions and weight	63 x 42 x 25 mm / ~ 60 g	
Cable lenght	30 cm, 3m or 8m	30 cm or 3m
Power supply	3,6v Lithium battery - Replaceable	
Battery life	6 years	
Fixation	Fixing eyelets and integrated magnets	
Supplied with	Blue JRI identification ring	Yellow identification ring
	User manual can be download on www.jri-corp.com	
Compliance	CE, ROHS, FCC, ETS 300-328, EN 12830	
Standard calibration points	-18°C/+6°C/+22°C	+36°C/+38°C/+45°C
Standard calibration points	-10 C/ +0 C/ +22 C	+30 C/ +30 C/ +43 C

Benefits

Easy-to-use

The sensor is ready to use and has operating and alarm lights



Excellent measurement accuracy .



Fixing eyelets



Replaceable battery and non disconnectable probe



Incubator Version

PART NRS 11569_EU : Nano SPY T2 30cm 11570_EU : Nano SPY T2 3m 11571_EU : Nano SPY T2 8m 11569_I_EU : Nano SPY T2 30cm 11570_I_EU : Nano SPY T2 3m

JRI, SAS

Logistics Pole / 2 Rue de la Voivre / PA Technoland / BP 21 / 25490 FESCHES LE CHÂTEL / France SIRET 380 332 858 00030 - Ph.: +33 (0)3 81 30 68 04 / sales@group-mms.com

Head office: 16 Rue Louis Rameau / CS 90050 / 95872 BEZONS Cedex / France / APE 2651B / TVA FR 02 380 332 858

www.jri-corp.com